



# SMK



The SMK is a 1U single-rail, rackmount monitor drawer with a 17" or 19" LCD, keyboard and touchpad. You have the option of choosing between a 1, 8, or 16 port KVM Switch.

The LCD is built into the cover, and the keyboard and touchpad are built into the base. Setup is fast and easy. Slide the console out; flip the cover up; and you are ready to work. Overall, the SMK simplifies IT duties, and makes installation processes hassle-free.

Occupying a fraction of the space of traditional monitor and keyboard units, the installation of the SMK leaves ample space for other critical components. With built-in analog-to-digital conversion board, the SMK can be connected to any standard VGA graphics card for immediate On Screen Display. The monitor key-board unit has a built-in slide rail and mounts easily onto any 19" rackmount cabinet.



**SMK 920**



**SMK 980**



**SMK 990**



**USB/PS2**



**USB/PS2**



**PS2**



**PS2**

## SMK Technical Specifications

| Model                    | SMK 920  | SMK 980   | SMK 990 |
|--------------------------|--|---|---------|
| <b>Dimensions/Weight</b> | 1.73" x 17.42" x 21.65"<br>(H x W x D) / 26.5 lbs<br>44mm x 442mm x<br>550mm (H x W x D) /<br>12.02 kg | 1.73" x 17.42" x 23.62" (H x W x D) /<br>28.7 lbs<br>44mm x 442mm x 600mm (H x W x D)<br>/ 13.02 kg |         |
| <b>Display</b>           | 17" or 19", 5:4 Display, 1280x1024   |   |         |
| <b>Brightness</b>        | 300 cd/m2<br>(Optional 1000 cd/m2)   |   |         |
| <b>Contrast Ratio</b>    | 500:1  |   |         |
| <b>Viewing Angle</b>     | 170° (H) x 160° (V)  |   |         |
| <b>Color</b>             | 262k Colors  |   |         |
| <b>Backlight MTBF</b>    | 50,000 Hours under 25±5°C  |   |         |
| <b>Power Supply</b>      | 60W, 100-240VAC, 50/60Hz   |   |         |
| <b>Keyboard/Mouse</b>    | 105-key cherry switch keyboard with touchpad   |   |         |

Specs subject to change. Customizations available through sales rep.

## Environmental Specifications

|                              |                        |
|------------------------------|------------------------|
| <b>Operating Temperature</b> | 0-50°C (32-122°F)      |
| <b>Approval</b>              | CE, FCC, UL, CCC, RoHS |

# Acme Portable Machines, Inc.

Contact us to request a quote today!



Headquarters - USA  
ACME Portable Machines, Inc  
1330 Mountain View Circle  
Azusa, CA 91702, USA  
Tel: +1 626.610.1888  
Fax: +1 626.610.1881  
[www.acmeportable.com](http://www.acmeportable.com)

Germany  
ACME Portable Computer GmbH  
Benzstraße 15  
76185 Karlsruhe, Germany  
Tel: +49.721.570.4530  
Fax: +49.721.570.45329  
[www.acmeportable.de](http://www.acmeportable.de)

Taiwan  
ACME Portable Corp.  
5F, No 25, Wuquan 3rd Road,  
Wugu Dist., New Taipei City 248, Taiwan R.O.C  
Tel: +886.2.2298.3636  
Fax: +886.2.2298.3737  
[www.acmeportable.com.tw](http://www.acmeportable.com.tw)